

AUXILIARY OIL COOLER

MADE IN THE USA!! Designed For use on Harley's without Lower Fairings as a Second Oil Cooler

INSTRUCTIONS

(Please read all instructions before beginning install)

Parts included

- 1- Deluxe Jagg Oil Cooler
- 1- Pair of Rubber Mounting Clamps w/ bolts & nuts
- 1- 22" Length of oil line hose
- 4- Black hose clamps
- 2- Zip ties

Installation Steps:

1. Place the Rubber Mounting Clamps around the left side down tube, one above the crossmember and one below it.

2. Mount the Oil Cooler to the Rubber Mounting Clamps, using the included hardware. Do not tighten all the way at this time. (it helps to use channel locks to pinch the rubber clamps together to start the bolts threading into the nuts)

3. Line up the Oil Cooler so that it is where you want it to be. For best cooling, it should lined up so that the air from the front flows directly through the fins of the cooler. Now you can tighten it down. Remember to use thread-locker on all fasteners.

4. Decide which oil cooler line is the easiest to access off your existing oil cooler. Remove this line from the oil cooler and from the engine. Using the supplied oil line, with hose clamps, route the oil line from your existing oil cooler to one side of your New Auxiliary Jagg Oil Cooler. Now from the other side of the New Oil Cooler, route the oil line, with clamps, back to the engine and tighten all clamps. 5. Use the supplied zip ties to secure the hoses.

6. Check your oil level (before starting the engine, and then again after it has run for a minute or two), & verify there are no leaks.

7. Go for a ride and be sure to check your oil level again after at least 30 minutes of constant riding.

Important Notes:

- The rider's safety depends on the correct installation of this kit. Please do not attempt if you have any doubts of your ability to install.
- Blue Thread locker (medium) MUST be used on all threads.
- It is recommended that periodic inspection (at least every 5000 miles) is made of the hose to verify there are no contact points creating wear.

www.DKCustomProducts.com