



## ***Deluxe Option for Tank Lift Kits Softail - Touring Models***

### **INSTRUCTIONS**

(Please read entire sheet before beginning install)

#### **Parts included:**

- 2 Lift Spacers
- 2 Bolts
- 2 Fender washers

(some bikes only require 1 lift spacer and bolt, so you may end up with an extra)

#### **Installation Steps:**

\*NOTE- For Touring Models- To get full benefit of this kit there needs to be a Tank Lift Kit installed on the front of the tank. Without a front Tank Lift Kit it will raise the rear of the tank, but will not be able to move the tank rear-ward.

1. Remove Seat
2. Remove the rear tank bolt. On later touring models (08+) there are two rear tank bolts.
3. Loosen the front tank bolts, top and bottom. (do not remove, they only need to be loose enough to allow some pivoting movement.
4. Carefully lift the back of the tank up and slide the Lift Spacer(s) between the frame and the bottom of the rear tank bracket(s). Slide the supplied bolt(s) through the tank bracket and Lift Spacer(s) into the frame. (On Touring Models, do not tighten all the way) On some Softails you will need to use the supplied fender washer(s) to keep the spacer from falling into the frame tube.

5. Now that you have the tank reattached, on Touring Models you can move the entire tank forward or rear-ward. Most of the time moving the tank rear-ward to obtain additional clearance between the handlebars and the front of the tank is most beneficial.
6. Once the tank is in the desired position, tighten ALL bolts and nuts. Top and bottom, front and rear.
7. Install seat and go for a ride!!!

***This Deluxe Option is especially useful on 2009+ Batwing bikes because moving the tank back allows for a higher lift in the front without interference from the inner fairing.***

***The top rockers will now be more visible and accessible for cleaning. You will have more air-flow over the engine. If you pivoted the tank rear-ward you will have additional clearance between the tank and the handlebars. Your gas gauge will read closer to stock than with just a front Tank Lift.***

**General Notes:**

- The riders safety depends on the correct installation of this kit. Please do not attempt if you have any doubts of your ability to install.
- We recommend blue thread locker be used on all threads.
- Installing this tank lift will result in a slight weight distribution change on your bike.
- Steering may feel a bit quicker. Exercise caution as you get accustomed to the slightly higher center of gravity.